

# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Addiese: COMMISSIONER FOR PATENTS P O Box 1450 Alexandra, Virginia 22313-1450 www.wepto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/576,783	04/21/2006	Makoto Katayama	MAT-8842US	5881
52473 7590 01/13/2011 RATNERPRESTIA			EXAM	INER
P.O. BOX 980			BAYOU, AMENE SETEGNE	
VALLEY FOR	RGE, PA 19482	ART UNIT	PAPER NUMBER	
			3746	
			MAIL DATE	DELIVERY MODE
			01/13/2011	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

# Office Action Summary

Application No.	Applicant(s)
10/576,783	KATAYAMA ET AL.
Examiner	Art Unit
AMENE S. BAYOU	3746

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS,

- WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

  Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filled after SIX (6) MONTHS from the mailting date of this communication.

earned patent term adjustment.	See 37 CFR 1.704(b).
--------------------------------	----------------------

- Failu Any	Deriod for reply is specified above, the maximum are to reply within the set or extended period for rep reply received by the Office later than three months and patent term adjustment. See 37 CFR 1.704(b).	ly will, by statute, cause the application	pire SIX (6) MONTHS from the mailing date of this communication to become ABANDONED (35 U.S.C. § 133), unication, even if timely filed, may reduce any	ation.
Status				
2a) 🛛	Responsive to communication(s) fi This action is FINAL. Since this application is in condition closed in accordance with the prac-	2b) This action is non- n for allowance except for	formal matters, prosecution as to the merits	s is
Disposit	ion of Claims			
5)□ 6)⊠ 7)□	Claim(s) <u>1-3 and 5-12</u> is/are pendir 4a) Of the above claim(s) is/a Claim(s) is/are allowed. Claim(s) <u>1-3 and 5-12</u> is/are rejectc Claim(s) <u>is/are</u> objected to. Claim(s) are subject to restr	are withdrawn from consided.		
9)□ 10)⊠	Applicant may not request that any obj Replacement drawing sheet(s) including	06 is/are: a)  accepted of accepted of accepted of accepted to accepted to accepted it	or b)	٠, ,
Priority (	under 35 U.S.C. § 119			
a)	Acknowledgment is made of a clain  All b	y documents have been re y documents have been re s of the priority documents onal Bureau (PCT Rule 1	eceived. eceived in Application No s have been received in this National Stage 7.2(a)).	
2) Notic 3) Infor	nt(s) ce of References Cited (PTO-892) se of Drawing-Review- mation Disclosure Statement(s) (PTO/SB/08 er No(s)/Mail Date			
Pape				

Art Unit: 3746

### DETAILED ACTION

### Claim Rejections - 35 USC § 103

 The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

- Claims 1-3, 6-10, 11 and 12 are rejected under 35 U.S.C 103(a) as being unpatentable over Katayama (Japanese patent publication number 2003065236) in view of Wantanabe (5076226).
- In re claims 1, 6, 8, 11 and 12 Katayama discloses a compression system including:
  - A hermetic compressor (figure 1) storing oil in a hermetic container and accommodating a compression mechanism for compressing refrigerant gas, wherein the compression mechanism comprises: a crank shaft disposed in vertical direction, and having a main shaft (9) and an eccentric shaft (10), a block forming a cylinder (13), a piston (23a) making a reciprocating motion in the cylinder (13), and having a top surface and a skirt surface, both vertical to a direction of the reciprocating motion, a connecting rod (11) for coupling the eccentric shaft (10) and the piston (23), and an oil supply system (7c) for supplying the oil to an outer circumference of the piston (see abstract), grooves (23e) are provided at an upper side and a lower side of the outer circumference of the piston, and of an outer shape of the grooves, the outer shape of the

Art Unit: 3746

grooves communicating with a space in the hermetic container at least when the piston is in a bottom dead center is a shape not forming a parallel line to an axial center of the piston when the grooves are developed in a plane (clearly shown in figure 5 and discussed in abstract), wherein a through-hole is disposed at about the center of the grooves (figure 5). Katayama ,however fails to disclose the following details of the grooves as taught by Watanabe et al:

- The outer shape of the grooves (28 and 328;figure 2,4,9) is a contiguous semicircular shape (column 3,lines 5-9;column 4,lines 6-18) extending toward a skirt side of the piston, and the semicircular shape includes a first outer shape extending toward the skirt side of the piston, a second outer shape parallel to the top surface of the piston, and a third outer shape linking the first outer shape and the second outer shape, and a curvature of the first outer shape is smaller than that of the third outer shape (figures 2,4,9 and 12 are different embodiments describing various shapes with different curvatures). It would have been obvious to one skilled in the art at the time the invention was made to modify the piston grooves of Katayama by making them in a contiguous semicircular fashion as taught by Watanabe et al. to increase the area of lubrication. Please note that once modified the grooves of Katayama communicate with the space in the hermetic compressor.
- In re claim 2 Katayama in view of Watanabe et al. as applied to claim 1 discloses the claimed invention:

Art Unit: 3746

Katayama discloses:

• All of the outer shape of the grooves (23e) are shapes not forming the

parallel line to the axial center of the piston when the grooves are

developed in a plane, in figure 5.

5. In re claim 3 Katayama in view of Watanabe et al. as applied to claim 1

disclosed the claimed invention but is silent as to how much the depth of the

groove is. But it would have been obvious to one skilled in the art at the time the

invention was made to choose the proper dimension of the grooves since such

choice merely depends on the size of the compressor ,the degree of lubrication

required and the flow rate of the lubricant that the designer chooses.

6. In re claims 6 and 10 Katavama in view of Watanabe et al. discloses the

claimed invention:

Katayama discloses:

A hermetic compressor ,in figure 1,storing oil in a hermetic container and

accommodating a compression mechanism for compressing refrigerant

gas, wherein the compression mechanism comprises: a crank shaft

y--, .....

disposed in vertical direction, and having a main shaft (9) and an

eccentric shaft (10) ,a block forming a cylinder ,a piston (23a) making a

reciprocating motion in the cylinder (13) , and having a top surface and a  $\,$ 

skirt surface, both vertical to a direction of the reciprocating motion, a

connecting rod (11) for coupling the eccentric shaft (10) and the piston

(23), and an oil supply system (7c) for supplying the oil to an outer

circumference of the piston (see abstract), grooves (23e) are provided at

Art Unit: 3746

an upper side and a lower side of the outer circumference of the piston, wherein a through-hole is disposed at about the center of the grooves (figure 5).

#### Watanabe et al teach:

- The grooves (28 and 328;figure 2,4,9) include a first portion extending toward a skirt side and a second groove portion extending toward a top side of the piston ,The first and second groove portions (28 and 328;figure 2,4,9) having contiguous semicircular shape (column 3,lines 5-9;column 4,lines 6-18). Please note that once modified the grooves of Katayama communicate with the space in the hermetic compressor.
- 7. In re claims 7 and 9 Katayama in view of Watanabe et al discloses the claimed invention since Watanabe et al's various embodiments (such as figure 9) clearly disclose that the outer shape of the groove including the first outer shape, the second outer shape and the third outer shape is a curved shape to be gradually increase in sliding width toward the skirt direction of the piston.
- 8. In re claim 11 Katayama in view of Watanabe et al discloses the claimed invention:

### Katayama discloses:

 A hermetic compressor, in figure 1, storing oil in a hermetic container and accommodating a compression mechanism for compressing refrigerant gas, wherein the compression mechanism comprises: a crank shaft disposed in vertical direction, and having a main shaft (9) and an eccentric

Art Unit: 3746

shaft (10) ,a block forming a cylinder ,a piston (23a) making a reciprocating motion in the cylinder (13) , and having i)a top surface and a skirt surface, both vertical to a direction of the reciprocating motion and II ) a through hole , a connecting rod (11) for coupling the eccentric shaft (10) and the piston (23), and an oil supply system (7c) for supplying the oil to an outer circumference of the piston (see abstract),grooves (23e) are provided at an upper side (or a lower side) of the outer circumference of the piston

### Watanabe et al teach:

• Grooves (28,328) are provided at an upper and a lower side of the outer circumference of the piston; The outer shape of grooves (28 and 328;figure 2,4,9) is contiguous semicircular shape (column 3,lines 5-9;column 4,lines 6-18) extending toward the skirt side of the piston, and the semicircular shape includes a first outer shape extending toward the skirt side of the piston, a second outer shape parallel to the top surface of the piston, and a third outer shape linking the first outer shape and the second outer shape, and a curvature of the first outer shape is smaller than that of the third outer shape (figures 2,4,9 and 12 are different embodiments describing various shapes with different curvatures). Please note that once modified the grooves of Katayama communicate with the space in the hermetic compressor when the piston is at BDC and the grooves do not form a parallel line to an axial center of the piston (please refer to the annotated drawing below). Please also note that since the grooves Watanabe et all are

Application/Control Number: 10/576,783 Art Unit: 3746

in a circular or semicircular fashion once modified the grooves will encompass (encircle) the through hole of Katayama.

9. In re claim 12 Katayama in view of Watanabe et all discloses the claimed invention:

## Katayama discloses:

• A hermetic compressor, in figure 1, storing oil in a hermetic container and accommodating a compression mechanism for compressing refrigerant gas, wherein the compression mechanism comprises: a crank shaft disposed in vertical direction, and having a main shaft (9) and an eccentric shaft (10), a block forming a cylinder, a piston (23a) making a reciprocating motion in the cylinder (13), and having a top surface and a skirt surface, both vertical to a direction of the reciprocating motion, a connecting rod (11) for coupling the eccentric shaft (10) and the piston (23), and an oil supply system (7c) for supplying the oil to an outer circumference of the piston (see abstract), grooves (23e) are provided at an upper side (or a lower side) of the outer circumference of the piston, wherein a through-hole is disposed at about the center of the grooves (figure 5), a sliding surface is provided all around a skirt side of the piston.

#### Watanabe et al teach:

Grooves (28,328) are provided at an upper and a lower side of the outer circumference of the piston; The outer shape of grooves (28 and 328;figure 2,4,9) is contiguous semicircular shape (column 3,lines 5-9;column 4,lines 6-18) extending toward the skirt side of the piston, and

Art Unit: 3746

the semicircular shape includes a first outer shape extending toward the skirt side of the piston, a second outer shape parallel to the top surface of the piston, and a third outer shape linking the first outer shape and the second outer shape, and a curvature of the first outer shape is smaller than that of the third outer shape (figures 2,4,9 and 12 are different embodiments describing various shapes with different curvatures). Please note that once modified the grooves of Katayama communicate with the space in the hermetic compressor when the piston is at BDC and the grooves do not form a parallel line to an axial center of the piston (please refer to the annotated drawing below).

- Claim 5 is rejected under 35 U.S.C 103(a) as being unpatentable over
   Katayama (Japanese patent publication number 2003065236) in view of Wantanabe
   (5076226) as applied to claim 1 further in view of Irino (5092747).
- 11. In re claim 5 Katayama discloses the claimed invention but fails to teach a CFC-12 type of refrigerant. But Irino in paragraph 1,lines 32-34 teaches that hydrocarbon refrigerants are widely used in refrigerant compressor. It would have been obvious to one skilled in the art at the time the invention was made to choose a CFC-12 or other hydrocarbon as refrigerant since it is one of the most commonly used refrigerant in the field.


Art Unit: 3746

## Response to Arguments


 Applicant's arguments with respect to claims 1-3 and 5-10 have been considered but are not persuasive.

13. Regarding claim 1 Applicants on page 4 paragraph 1 argued that Grooves 28 and 328 of Wantanbe et al. do not show a second outer shape parallel to the top surface of the piston and also asserted that same grooves fail to show a third outer shape linking the first outer shape and the second outer shape. Examiner respectfully disagrees.

Similar to the limitation of claim 1, Wantanbe in column 3,lines 5-9; column 4,lines 6-18 clearly stated that both grooves 28 and 328 are fashioned in a semicircular way to facilitate supply of oil to the piston surface. The figures reproduced below also clearly illustrate that the groves essentially comprise 3 shapes similar to Applicants' invention.



Art Unit: 3746



As shown in the annotated figures above a curvature of the first outer shape is smaller than that of the third outer shape.

Art Unit: 3746

#### Conclusion

 THIS ACTION IS MADE FINAL. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Amene S. Bayou whose telephone number is 571-270-3214. The examiner can normally be reached on miff attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Devon Kramer can be reached on 571-272-7118. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR

Page 12

Application/Control Number: 10/576,783

Art Unit: 3746

only. For more information about the PAIR system, see http://pair-

direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-

free). If you would like assistance from a USPTO Customer Service

Representative or access to the automated information system, call 800-786-

9199 (IN USA OR CANADA) or 571-272-1000.

/Devon C Kramer/ Supervisory Patent Examiner, Art Unit 3746

/Amene S Bayou/

Examiner, Art Unit 3746